


HM2301BJR P-Channel MOSFET

V_{(BR)DSS}	R_{DS(on)MAX}	I_D
-20V	500mΩ@-4.5V	-0.80A
	750mΩ@-2.5V	
	780mΩ (TYP)@-1.8V	




FEATURE

- Lead Free Product is Acquired
- Surface Mount Package
- P-Channel Switch with Low R_{DS(on)}
- Operated at Low Logic Level Gate Drive


APPLICATION

- Load/Power Switching
- Interfacing, Logic Switching
- Battery Management for Ultra Small Portable Electronics

MARKING



Equivalent Circuit



Maximum ratings (T_a=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	-20	V
Typical Gate-Source Voltage	V _{GS}	±12	V
Continuous Drain Current (note 1)	I _D	-0.80	A
Pulsed Drain Current (t _p =10 μ s)	I _{DM}	-2.4	A
Power Dissipation (note 1)	P _D	150	mW
Thermal Resistance from Junction to Ambient (note 1)	R _{θJA}	833	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55~+150	°C
Lead Temperature for Soldering Purposes(1/8" from case for 10 s)	T _L	260	°C

MOSFET ELECTRICAL CHARACTERISTICS







HM2301BJR




$T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
STATIC CHARACTERISTICS						
Drain-source breakdown voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = -250\mu\text{A}$	-20			V
Zero gate voltage drain current	I_{DSS}	$V_{\text{DS}} = -20\text{V}, V_{\text{GS}} = 0\text{V}$			-1	μA
Gate-body leakage current	I_{GSS}	$V_{\text{GS}} = \pm 10\text{V}, V_{\text{DS}} = 0\text{V}$			± 20	μA
Gate threshold voltage (note 2)	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = -250\mu\text{A}$	-0.4	-0.7	-1.0	V
Drain-source on-resistance (note 2)	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = -4.5\text{V}, I_D = -1\text{A}$		410	500	$\text{m}\Omega$
		$V_{\text{GS}} = -2.5\text{V}, I_D = -0.8\text{A}$		575	750	$\text{m}\Omega$
		$V_{\text{GS}} = -1.8\text{V}, I_D = -0.5\text{A}$		780	1100	$\text{m}\Omega$
Forward transconductance (note 2)	g_{fs}	$V_{\text{DS}} = -10\text{V}, I_D = -0.54\text{A}$		1.2		S
Diode forward voltage	V_{SD}	$I_S = -0.5\text{A}, V_{\text{GS}} = 0\text{V}$			-1.2	V
DYNAMIC CHARACTERISTICS (note 4)						
Input capacitance	C_{iss}	$V_{\text{DS}} = -16\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		113	170	pF
Output capacitance	C_{oss}			15	25	pF
Reverse transfer capacitance	C_{rss}			9	15	pF
SWITCHING CHARACTERISTICS (note 4)						
Turn-on delay time (note 3)	$t_{\text{d}(\text{on})}$	$V_{\text{GS}} = -4.5\text{V}, V_{\text{DS}} = -10\text{V}, I_D = -200\text{mA}, R_{\text{GEN}} = 10\Omega$		9		ns
Turn-on rise time (note 3)	t_r			5.8		ns
Turn-off delay time (note 3)	$t_{\text{d}(\text{off})}$			32.7		ns
Turn-off fall time (note 3)	t_f			20.3		ns

Notes :

1. Surface mounted on FR4 board using the minimum recommended pad size.
2. Pulse Test : Pulse Width=300 μs , Duty Cycle=2%.
3. Switching characteristics are independent of operating junction temperatures.
4. Guaranteed by design, not subject to producting.


Output Characteristics**Transfer Characteristics** **$R_{DS(ON)}$ — I_D**  **$R_{DS(ON)}$ — V_{GS}**  **I_S — V_{SD}** **Threshold Voltage**



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.430	0.500	0.017	0.020
A1	0.000	0.050	0.000	0.002
b	0.170	0.270	0.007	0.011
b1	0.270	0.370	0.011	0.015
c	0.080	0.150	0.003	0.006
D	1.150	1.250	0.045	0.049
E	1.150	1.250	0.045	0.049
E1	0.750	0.850	0.030	0.033
e	0.800TYP.		0.031TYP.	
θ	7° REF.		7° REF.	

SOT-723 Suggested Pad Layout


HM2301BJR



Note:

1. Controlling dimension:in millimeters.
- 2.General tolerance: $\pm 0.05\text{mm}$.
- 3.The pad layout is for reference purposes only.

SOT-723 Embossed Carrier Tape




Packaging Description:


SOT-723 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 8,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-723	1.33	1.45	0.61	Ø1.50	1.75	3.50	4.00	2.00	2.00	8.00

SOT-723 Tape Leader and Trailer



SOT-723 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
8000 pcs	7 inch	120,000 pcs	203×203×195	480,000 pcs	438×438×220	